

SWIFT RH SERIES FLUSH MOUNTING RANGE HOOD

This series of Range Hood is designed to fit into the underside of eye level cupboards. It covers the underside of the cupboard for the full width of the Swift 500 series cookers so there is no need for further protection of the timber for excess heat.

INSTALLATION

There are two methods of fixing the range hood into the cavity, either produce a cupboard with an additional shelf board 62 mm above the opening through which four 4mm screws can be used to draw the range hood up into the cavity or the face of the range hood can be removed and the body of the range hood can be mounted using screws through the flange.

CUT OUT SIZE

The cut out size is 465mm x 187mm

BENCH CLEARANCE

The minimum height clearance to the cooker surface is 450mm or for the Swift 500 series cookers because the there cooking surface is 50mm lower than the bench it means that it can be mounted 400mm above the bench surface

INSTALLING WITH A FLUE PIPE

1. Ensure that the panel to which the range hood is to be mounted is secure.
2. The flue can be connected either out the rear or the top. Cut out a 60mm diameter hole in line with the opening in the range hood. Ensure that the hole is above the height of the face of the range hood for rear discharge connection.
3. Remove the flue connector plate and position the flue into the opening. Secure the plate down over the flue.
4. Connect the 12 Volt DC supply ensuring correct polarity
5. Now fix the unit into the cavity using either the top or bottom fixing method.

OPERATION

Always place pans over the burners when using the cooktop.

Light can be used at any time.

Turn fan on when you have a burner operating.

Note The unit is supplied with a 20 watt lamp. These long life lamps can be sourced from general stores or electrical parts stores.

CLEANING

Regularly wipe over a damp soap cloth to avoid fat build up on the filter plate and leading edge.

SERVICE

If you require service of your SWIFT Rangehood please phone (03) 9359 3068 or fax (03) 9357 2279 or if outside Australia, contact the dealer from which you purchased the rangehood.

Any correspondence can be mailed to the Manufacturer:

Casale Trim Co Pty Ltd, 25 – 27 Brooklyn Court Campbellfield Victoria Australia 3068
or Email : swiftag@myplace.net.au

WARRANTY

Casale Trim Co Pty Ltd warrants the purchaser against defects in workmanship for a period of 12 months from the date of purchase. This record is to be retained as proof of purchase and must be presented if making a claim.

Casale Trim Co Pty Ltd reserve the right to replace or repair the rangehood during the warranty period.

The warranty does not apply to any defect, injury, loss or damage caused by or as a result of misuse of the rangehood.

This rangehood must only be serviced by an authorized person.

CONDITIONS

This warranty only applies in the Commonwealth of Australia and for appliances used for private domestic use.

Faults not rectified under this warranty

- (a) if the rangehood serial number has been altered or removed
- (b) if the fault is notified outside the warranty period.
- (c) To powder coated parts, vitreous enamel and glass

The purchaser shall be responsible for any expenses involved in making the rangehood readily accessible for servicing and transporting the rangehood to the nearest Casale Trim Co. Pty Ltd service agent or dealer.

The purchaser must provide proof of the date of purchase.

Complete the following to assist us should you require service under the terms of this warranty.

PURCHASED FROM _____

PURCHASE DATE _____ **MODEL NO.** _____

SERIAL NO: _____